1U 17" LCD KVM CONSOLE





- Monitor and compact keyboard with trackball or touchpad in 1U of rack space.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan[™] covering.



DISPLAY SPECIFICATIONS

Display Type: Resolution: Active matrix TFT LCD 640 x 350 Colors: 640 x 480 16.7 million colors 800 x 600 **Contrast Ratio:** RMM-3X7: 1000:1 typ. 1280 x 1024 **Brightness:** Display Area:

RMM-3X7: 280 cd/m2 typ.

Viewing Angle:

Horizontal: 170°

Vertical: 160° Response Time:

1024 x 768

17" Diagonal **Horizontal Frequency:**

31.5 to 80 KHz

Vertical Frequency: 56 to 75 Hz.

25ms.

KEYBOARD AND MOUSE SPECIFICATIONS

Alpha N-key rollover. Rollover:

Auto repeat: Yes.

Self Diagnostics: At power on and system reset. Data Buffer: All codes buffered before sending.

Operating voltage: +5 VDC +/- 5%. Operating current: 100 mA max. Trackball Size: 16mm. **Touchpad Size:** 2.1" X 1.25"

Buttons: Left and Right, Scroll(touchpad). Interface: Keyboard: PS/2 or USB(U).

Trackball: PS/2 or USB(U). Touchpad: PS/2 or USB(U).

Compatibility: Windows operating systems. Specifications subject to change without notice.

We offer OEM and custom solutions. Contact us for additional information.

Cherry™ KB w/trackball = 1 -Std KB w/ trackball = 3

Std KB w/touchpad = 5 -

GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 1.75" (H) x 20.80" (D)

Weight:

25 lbs

Power (TFT Display):

90 - 260 VAC, 50/60 Hz. 60 Watts maximum

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load

and Save Values

Plug & Play:

DDC1 and DDC2B

Temperature:

0°C to 50°C Operating: Storage: -20°C to 60°C

Humidity:

Operating: 10 to 85% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Connector:

15-pin mini D-Shell Display:

Colors Available: Black.

MODEL NUMBER

LTRM-3(X)7(X) Blank = Standard Front Panel R = Front Panel + Retainer Screws L = Front Panel + Lock C = Front panel + Lock + Retainer

1-800-660-2286

www.lantekrackmount.com

lantek@earthlink.net

P. O. Box 549 Yucca Vallley, CA 92286

Tel: 760-364-2900 Fax: 760-364-4997