

1U 17" LCD KVM CONSOLE



- Monitor and keyboard with two button touchpad in 1U of rack space.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan™ covering.

DISPLAY SPECIFICATIONS

Display Type: Active matrix TFT LCD	Resolution: 640 x 350 640 x 480 800 x 600 1024 x 768 1280 x 1024
Colors: 16.7 million colors	Display Area: 17" Diagonal
Contrast Ratio: 1000:1 typ.	Horizontal Frequency: 31.5 to 80 KHz
Brightness: 250 cd/m ² typ.	Vertical Frequency: 56 to 75 Hz.
Viewing Angle: Horizontal: 170° Vertical: 160°	
Response Time: 5ms.	

KEYBOARD AND TOUCHPAD SPECIFICATIONS

Rollover:	Alpha N-key rollover.
Auto repeat:	Yes.
Self Diagnostics:	At power on and system reset.
Data Buffer:	All codes buffered before sending.
Operating voltage:	+5 VDC +/- 5%.
Operating current:	200 mA.
Touchpad Size:	2.2" X 1.6"
Buttons:	Left and Right.
Interface:	Keyboard: PS/2 or USB (U). Touchpad: PS/2 or USB (U).
Compatibility:	Windows operating systems. Specifications subject to change without notice.

We offer OEM and custom solutions.
Contact us for additional information.



GENERAL SPECIFICATIONS

Dimensions:	19.0" (W) x 1.75" (H) x 25.75" (D)
Weight:	27 lbs
Power (TFT Display):	90 - 260 VAC, 50/60 Hz. 60 Watts maximum
On-Screen Controls:	Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values
Plug & Play:	DDC1 and DDC2B
Temperature:	Operating: 0°C to 50°C Storage: -20°C to 60°C
Humidity:	Operating: 10 to 85% RH (max)
Input Signal (VGA):	R.G.B. analog video, TTL H & V sync.
Input Connector:	Display: 15-pin mini D-Shell
Colors Available:	Choice of Black (B) or Light Gray.

MODEL NUMBER

LTRM-617(X)

—	Blank = Standard Front Panel
—	R = Front Panel + Retainer Screws
—	L = Front Panel + Lock
—	C = Front panel + Lock + Retainer Screw

LAN TEK

www.lantekrackmount.com
lantek@earthlink.net

1-800-660-2286

P. O. Box 549
Yucca Valley, CA 92286
Tel: 760-365-2900
Fax: 760-364-4997