

# 17" RACK MOUNT LCD MONITOR



- 17" LCD display (1280 x 1024 resolution) in 7U (12.25") of rack space.
- Fast video response time for sharp text and crisp motion.
- 1000:1 Static contrast ratio provides superior detail.
- Optional Lexan™ (L) or 5 wire resistive touchscreen (T).
- Optional NTSC Composite Video and S-Video inputs (V) .

## GENERAL SPECIFICATIONS

### Dimensions:

19.0" (W) x 12.3" (H) x 1.75" (D)

### Weight:

9.5 lbs.

### Power:

110 - 240 VAC, 50/60 Hz.  
60 Watts max.

### Plug & Play:

DDC1 and DDC2B

### Temperature:

Operating: 0°C to 50°C  
Storage: -20°C to 60°C

### Humidity:

Operating: 10 to 90% RH (max)

### Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

### Input Signal (Digital):

DVI-D (TDMS).

### Input Connectors:

Analog: 15-pin mini D-Sub.  
Digital: 24 pin DVI-D.

### Compatibility:

PC/Windows, Macintosh.

### Colors Available:

Black.



## DISPLAY SPECIFICATIONS

### Display Type:

TFT active matrix LCD.

### Viewable Size:

17.0" diagonal.

### Colors Displayed:

16.7 million colors.

### Contrast Ratio :

1000:1.

### Brightness:

250 cd/m<sup>2</sup> typ.

### Viewing Angles:

170°/160° H/V.

### Response Time:

5 ms Typ.

### Optimum Resolution

1280 x 1024..

### Light Source:

Long Life (50,000 hrs typ).

### Panel Surface:

Anti-glare.

Specifications subject to change without notice.

## MODEL NUMBER

LTRM-917/XX

- Blank = Standard Screen.
- L = Lexan™ Screen Protection.
- T = 5 Wire Resistive Touch Screen.
- Blank = ARGB and DVI-D Inputs.
- V = Composite NTSC, S-Video, ARGB and DVI-D Inputs.

Offering OEM and custom solutions.  
Contact us for additional information.



**LAN TEK**

[www.lantekrackmount.com](http://www.lantekrackmount.com)

[lantek@earthlink.net](mailto:lantek@earthlink.net)

**1-800-660-2286**

P. O. Box 549  
Yucca Valley, CA 922

Tel: 760-364-2900  
Fax: 760-364-4997