

LAN TEK

AutoView 1400 KVM Switch



The AutoView® 1400 KVM switching system includes multi-platform support, advanced cable management options and a convenient on-screen display.

Features and Benefits

Avocent® AutoView 1400 8-port, single user KVM switch provides PS/2, USB, Sun and serial connectivity, advanced cabling options, flexible access and a next-generation user interface in one switching solution.

The AutoView 1400 switch server interface modules and integrated access cables automatically assign and retain unique server names, which simplifies installation and eases re-configuration. With flexible cable options and advanced on-screen management, the AutoView 1400 switching system is an ideal solution for today's small office and mid-sized business networking environments.

- Integrated access cables offer PS/2 or USB keyboard, video and mouse connectivity in one, slim CAT 5 cable, which reduces cable bulk, saves time and reduces cost.
- Server interface modules support all major server platforms and VT100 serial-based devices.
- Provides access to eight PCs and network devices.
- Advanced on-screen management provides easy configuration and server selection.
- BIOS-level access ensures connection to the attached servers regardless of the health or type of operating system.
- A space-saving 1U rack mount design.
- Flash-upgrades firmware for fast and easy updates for appliances and server interface modules.
- Keep Alive power safeguard allows attached servers to continue network functions in the event of power failure to the AutoView switch.
- Includes rack mount kit.

| | | |
|----------------------|-------------------|---------------------------|
| Mechanical | Height | 1.75 in. (4.45 cm) |
| | Width | 17.00 in. (43.18 cm) |
| | Depth | 11.00 in. (27.94 cm) |
| | Weight | 8 lbs. (3.6 kg) |
| Environmental | Operating Temp | 50 to 122 F (10 to 50 C) |
| | Storage Temp | -4 to 140 F (-20 to 60 C) |
| Power | Operating Voltage | 100 - 240 VAC Autosensing |

| | | |
|---------------------------|-----------------------|--|
| | Power Frequency Input | 50/60 Hz 40 W Maximum |
| Supported Hardware | Computers | BM PC/AT, PC and 100% compatibles |
| | Monitors | XGA, XGA-II with adapter, 1600 x 1280 @ 75 Hz resolution |
| | Peripherals | PC keyboard, PC mouse, Microsoft Explorer mouse, Microsoft IntelliMouse family, IBM Scrollpoint, Logitech Mouseman Wheel, Logitech Trackman Marble Wheel, Logitech Marble FX and Kensington 4-button mouse |
| Standards | Approved Agency | UL FCC Class A, cUL, ICES Class A, CE, N, GS, IRAM, GOST, VCCI, Class A, MIC Class A, C-Tick |

LAN TEK
800.660.2286

Fax: 760.364.4997

Email: lantek@earthlink.net

Web: www.LAN-TEK.NET

P. O. Box 549

Yucca Valley, CA 92286